



 **ZORAKI**[®]

HY-01 SPRING



HY-01

SPRING

SINGLE PUMP SPRING PISTOL TECHNICAL SPECIFICATIONS

- Single shot
- Single strok
- New technology, double spring system
- Power storage system set up by spring when upper frame opened and closed
- Opening and closing of upper frame store the power in both way with minimum effort and gain maximum energy technology
- Automatic trigger safety
- Right and Left - Up and Down adjustable rear sight.
- Polymer frame with steel plate backed
- Plastic orthopedic grip with ergonomic design
- Recoil free shooting
- Rail for laser, binoculars, 'red dot' or any weight scope
- Rifled steel barrel & high corrosion resistance
- Elegant carrying case with allen key
- Cleaning rod, and oil

CAL.: 177-22 (4.5-5.5mm.)

Length: 336 mm.

Height: 179 mm.

Width: 50 mm.

Grip Width: 51 mm.

Weight: 1500 gr.

Safety Distance: 350 m.

Number of Rifled: Set 12

Steel Barrel Length: 295 mm.

Maximum Energy 7.5 joule cal. 4.5 mm 0.48 gr.

Muzzle Velocity: 170 m/s 0.48 gr.

 **ZORAKI**[®]



   - www.atakarms.com



2914



2914

TECHNICAL SPECIFICATIONS

- Semi Automatic - Double Action
- Mechanism lock by side button when out of cartridge
- Magazine release button at the side
- Hardened steel reinforced cock
- Hardened steel shell launcher and puller extractor
- Steel-reinforced zinc alloy mechanism (slide)
- Capability to shoot firework and signal flare
- New ergonomic grips design.

Caliber: 9 mm. P.A.K.

Barrel Length: 85 mm.

Overall Length: 159 mm.

Height: 125 mm.

Width: 35 mm.

Magazine Capacity: 14+1

Unloaded Weight: 735 gr.

Loaded Magazine Total Weight: 815 gr.

Number of Component: 47 pcs.

Ambient Operating Temperature: -15°... +50°



📷 📺 📱 - www.atakarms.com

ZORAKI®

